



OptoTech

SPO 130 CNC

Low-Priced CNC-Controlled Polishing Machine for Optics up to Ø 130 mm




The OptoTech polishing machine SPO 130 CNC is the ideal low cost version of a high speed CNC polisher. The universal working range and the easy usage combined with up to date polishing technology offer a machine with an unmatched price-performance ratio.



OptoTech

Datos técnicos

	SPO 130 CNC
Working Range Diameter	10 mm - 130 mm
Working Range Radius	+/- 10 mm to plano
Tool Spindle	Velocidad de giro: 30 - 1500 rpm, infinitely variable; Interfaz: HD 25
Workpiece Spindle	Velocidad de giro: 30 - 1500 rpm, infinitely variable; Interfaz: HD 25
Vacuum	-0.7 bar
Requisitos de presión de aire	5 bar
Requisitos eléctricos (otros bajo pedido)	9 kVA / 400 V / 5 0Hz
Dimensiones	Ancho: 1425 mm, Altura: 1990 mm, Profundidad: 1765 mm
Peso (aprox.)	2000 kg



Características destacadas

- Low-Priced CNC-controlled polishing machine with oscillation movement of the polishing tool around the lens center
- 2-spindle version (Workpiece Spindle and Tool Spindle)
- Kinematic with CNC controlled swivelling movement in the radii center
- Integrated polishing tool correction technology OCT (OptoTech Correction Technology)
- OptoTech user interface, Microsoft Windows
- Input of all parameters via dialogue menu

Ventajas del sistema

- Low-Priced CNC-controlled polishing machine
- Energy-efficient motors: Possible energy savings up to 30% (depending on required power)

Características de rendimiento

Standard cycles:

- Polishing in SynchroSpeed mode
- Dressing of polishing tools
- Other Technologies available on request

Opciones

- Exhaust Filter System for Mist Collection
- Polishing Tank
- Automatic handling for disk magazine and for DIN palette (with NC portal loader)



OptoTech